

MG 6000 SSY-5 – Tin 12

6kVA Tin 12 Diesel Generator

When looking for a robust, reliable, good quality 6kVA diesel generator, look no further than our MG 6000 SSY-5 – Tin 12.

Optional extras:



Stage 5 Engine



YANMAR
3 Year Engine Warranty (Limited)

Features Benefits

6kVA (110V only) AC Aux Power
Linz alternator
Yanmar electric start diesel engine (Stage 5)
HVO (Hydrotreated Vegetable Oil) fuel approved
Exclusive MHM engine protection shutdown system
Emergency stop button
Central lifting eye and front & side fork pockets
Fully bunded base (110%)
Complete with trolley kit + folding handles

Plenty of power to meet the demands of small to medium gas and water applications
Heavy duty, proven reliability and extra smooth wave form
Power, reliability and robust strength
Suitable to run off either diesel, HVO or a mixture of both fuels
In the case of low fuel, low oil pressure and battery charge failure
A must on any UK site
Flexible and safe lifting on site
To retain all spilt fluids
For nice and easy manoeuvrability, transport and storage



Specification

Performance

Alternator	Linz	Noise Level	LWA=90 dBa@7m=65
Single Phase Power (110V)	6kVA/ 4.8kW	Insulation Class	H
Single Phase Power (230V)	N/A	Mechanical Protection - IP	23

Engine

Make	Yanmar	Cooling	Air
Type	L100AE (Stage 5)	Fuel Consumption @ 75% Load (Litres/hour)	1.4
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Fuel Tank Capacity (Litres)	25
Number of Cylinders	1	Average Runtime @ 75% Load (Hours)	18
Power (HP)	10	CO ₂ Output Per Hour @ 75% Load	3.67kg
Engine Speed (RPM)	3000	Starting System	Deepsea 3110 c/w two wire Auto Start/ Stop facility

Dimensions (Machine only)

Length: 1050 mm	Width: 590 mm	Height: 750 mm
Dry Weight (No Fuel): 182 kg	Wet Weight (Fuel Full): 203 kg	

Dimensions (Trolley kit with handles folded out)

Length: 1570 mm	Width: 760 mm	Height: 980 mm
Dry Weight (No Fuel): 207 kg	Wet Weight (Fuel Full): 228 kg	

Dimensions (With road-tow kit)

Length: 2405 mm	Width: 1045 mm	Height: 1190 mm
Dry Weight (No Fuel): 312 kg	Wet Weight (Fuel Full): 333 kg	

Socket Configuration

MG 6000 SSY-5 – Tin 12	1ph (110V)	
	32A	16A
	1	2

For more details call **MHM TODAY**
on **0808 168 9099**

Email sales@mhmplant.com or visit us at www.mhmplant.com



GROUP
The Preferred Supplier

Designed in the UK,
built in Italy

