

# **MG 6500 RT**

## 6.5kVA Railtrack Approved Petrol Generator

When looking for robust, reliable, good quality 6.5kVA Railtrack Approved petrol generator, look no further than our MG 6500 RT.

Optional



Railtrack approved

6.5kVA (110V) CTE (55V-0-55V)

Mecce Alte alternator

Honda petrol engine

Special stackable-friendly

Strong wrap-around frame

Only 66kg

Extra large fuel tank

## Features Benefits

Trackside ready

Plenty of power to run a variety of tools on site

Heavy duty and proven reliability

Featuring low oil level shutdown

Simple and easy transport & storage

Great protection in a rail environment

Extremely light weight

Extra long run time



### Specification

Performance	
Alternator	Mecc Alte
Single Phase Power (110V)	6.5kVA/ 5.2kW
Single Phase Power (230V)	N/A

Three Phase Power (400V)	N/A
Noise Level LWA=96	dBa@7m=71
Insulation Class	Н
Mechanical Protection - IP	23

Engine	
Make	Honda
Туре	GX390
Fuel	Petrol
Number of Cylinders	1
Power (HP)	13
Engine Speed (RPM)	3000
Cooling	Air

Fuel Consumption @ 75% Load (Litres/hour)				
Fuel Tank Capacity (Litres)				
Average Runtime (Hours)				
@ 100% Load TBA	@ 75% Load	8		
@ 50% Load TBA	@ 25% Load	TBA		
Starting System		Recoil		

MG 6500 RT					1	2	
Configuration	32A	16A	32A	16A	32A	16A	
Socket	3ph (400V)		1ph (230V)		1ph (110V)		
Dry Weight (No Fuel): <b>TBA</b> kg Wet Weight (Fuel Full): <b>TBA</b> kg							
Length: TBA mm	Width: TBA mm Height: TBA mm						
<b>Dimensions</b> (Trolley kit with handles folded out)							
bry Weight (No Faci). 00 kg	Wet Weight (ruerruin). IDA kg						
Dry Weight (No Fuel): 66 kg	Wet Weight (Fuel Full): <b>TBA</b> kg						
Length: 800 mm	Width: 520 mm				Height: 556 mm		



Designed in the UK, built in Italy

All pictures are for illustration purposes only, actual machines supplied may differ in appearance and specification.

**Dimensions** (Machine only)

