

MG 10000 SSK-3PH

Ready to Rent 10kVA Diesel Generator

When looking for a robust, reliable, good quality 10kVA diesel

generator, look no further than our MG 10000 SSK-3ph



Optional extras:





10kVA (400V - 3ph) AC Aux Power

Linz alternator

Kubota diesel engine (Stage 3)

HVO (Hydrotreated Vegetable Oil) fuel approved

Exclusive MHM engine protection shutdown system

Emergency stop button

Central lifting eye and front & side fork pockets

Fully bunded base (110%)

Complete with trolley kit + folding handles

## Features Benefits

Plenty of power to meet the demands of small generator hire

Heavy duty and proven reliability

World class performance and watercooled

Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure and battery charge failure

A must on any UK site

Flexible and safe lifting on site

To retain all spilt fluids

For nice and easy manoeuvrability, transport and storage

## Water Cooled Extra Super Silent



くいりっけっ **2 Year Engine Warranty** (Limited)



# Specification

#### **Performance**

Linz
N/A
3.3kVA/ 2.6kW

Noise Level	LWA=89	dBa@7m=64
Insulation Class		Н
Mechanical Protect	ion – IP	23

#### **Engine**

Make	Kubota
Туре	D722E (Stage 3)
Fuel Diesel / HVO (HVO	= BS EN 15940:2016 Only)
Number of Cylinders	3
Power (HP)	17
Engine Speed (RPM)	3000
Cooling	Water

Fuel Consumption (	r) 2.8		
Fuel Tank Capacity	40		
Average Runtime (I			
@ 100% Load 11 @ 75% Load			
@ 50% Load	22	@ 25% Load	44
CO2 Per Hour @ 75% Load			7.34kg
Starting System  Deepsea 3110 c/w two wire Auto Start/ Stop facility			

Length: 1220 mm	Width: 670 mm	Height: <b>840</b> mm
Dry Weight (No Fuel): <b>350</b> kg		Wet Weight (Fuel Full): 381 kg

#### **Dimensions** (Trolley kit with handles folded out)

Length: 1635 mm	Width: 940 mm	Height: 980 mm
Dry Weight (No Fuel): 365 kg		Wet Weight (Fuel Full): 396 kg

### **Dimensions** (With road-tow kit)

Length: 2650 mm	Width: 1300 mm	Height: <b>1200</b> mm
Dry Weight (No Fuel): 485 kg		Wet Weight (Fuel Full): 516 kg

Socket	3ph (400V)		1ph (230V)	
Configuration	32A	16A	32A	16A
MG 10000 SSK-3ph	1	-	-	1
Hard wire facility	3ph (400V)		1ph (2	230V)
MG 10000 SSK-3ph	V		V	

For more details call MHM TODAY

on **0808 168 9099** 

**Email** sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk











